

UNITED STATES OF AMERICA
DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION
RENTON, WASHINGTON 98055-4056

In the matter of the petition of

Gulfstream Aerospace Corporation

for an exemption from § 25.901(c) of Title 14,
Code of Federal Regulations

Regulatory Docket No. FAA-2003-15118

PARTIAL GRANT OF EXEMPTION

By letter dated May 2, 2003, Richard J. Trusis, Director, Airworthiness/ Certification and Data Management, Gulfstream Aerospace Corporation, P.O. Box 2206, Savannah, Georgia 31402-2206, petitioned for a partial exemption from the “no single failure” criterion of § 25.901(c) of Title 14, Code of Federal Regulations (14 CFR) as it relates to “uncontrollable high thrust failure conditions.” Recent studies and service experience indicate that some existing transport category airplanes do not strictly comply with § 25.901(c) for certain uncontrollable high thrust failure conditions. The proposed partial exemption, if granted, would permit similarly noncompliant Gulfstream Models G-1159, G-1159A, G-1159B, G-IV, GV, and GV-SP derivative type design changes to be approved under Type Certificate Number A12EA after the date of the grant of partial exemption.

The petitioner requires relief from the following regulation(s):

Section 25.901(c) requires in part that “no single failure will jeopardize the safe operation of the airplane.”

The petitioner's request

Gulfstream's Request for Exemption, dated May 2, 2003, was submitted to the Docket Management System and given Docket Number FAA-2003-15118.⁽¹⁾ The entire document may be viewed by following the instructions in footnote (1).

An excerpt from the petition is provided below.

"Gulfstream Aerospace respectfully requests a partial exemption to Federal Aviation Regulation (FAR) Part 25.901(c) of Title 14, CFR, for certain extremely remote powerplant failures that could affect only a very limited portion of the flight envelope of the Gulfstream Model G-1159, G-IV, and GV type design changes to be approved under Type Certificate Number A12EA after the date of this granting. Granting this exemption would permit type certification of similarly non-compliant derivatives of the current Gulfstream A12EA Model airplanes and their future modifications/derivatives.

"The nature of this petition for partial exemption is similar to previously granted exemptions for the Airbus models A340-500 [and] A340-600, the Embraer models EMB-135BJ [and] EMB-145XR, the Boeing model 757-300, and the Gulfstream Model GV-SP."

"Gulfstream will demonstrate that the risks due to uncontrollable high thrust failure conditions on any airplane certificated under this partial exemption will not exceed those currently known and accepted for comparable existing transport category airplanes. This condition, in combination with the condition to minimize that risk, means that granting this partial exemption should not adversely affect and, in fact, should improve the average per flight hour risk within the current transport airplane."

"The engine control systems for the existing variants of the Gulfstream A12EA designs are all modern FADEC based systems and as such future design changes to these control systems should provide opportunities to significantly reduce or even eliminate the subject non-compliance."

Notice and Public Procedure Provided

A summary of this petition was not published in the Federal Register as the nature of this partial exemption is effectively identical to those of previous petitions for which there were no public comments received.

⁽¹⁾ The Docket Management System is available on the Internet at www.dot.gov. Select Dockets, then Docket Management System (DMS). Perform a Simple Search, entering the Docket Number. This will bring up a list of one or more documents which you may view and copy.

The Federal Aviation Administration's (FAA) analysis is as follows:

I. BACKGROUND

Uncontrollable High Thrust Failure Conditions

Numerous single and anticipated combinations of failures within traditional turbojet engine control systems result in losing the normal means to control thrust (i.e., control via the throttle lever, autothrottle, etc.). A subset of the resulting failure conditions may include actual thrust either increasing to higher than commanded and/or remaining high when low thrust is commanded. These “Uncontrollable High Thrust Failure Conditions” and the hazards they pose have long been inherent in transport airplane designs. In fact, the “fail-safe” states for engine controls have traditionally been chosen to protect high thrust capability and allow the flightcrew to decide when an engine shutdown is appropriate.

An initial estimate indicates that over the last 20 years the average rate of occurrence for the uncontrollable high thrust failure condition on turbofan-powered large transport category airplanes has remained relatively constant at around one every 2.5 million flight hours. This would indicate that to date an “Uncontrollable High Thrust Failure Condition” has occurred hundreds of times without resulting in a single reported serious injury.

When these failure conditions were identified during past certifications, compliance was typically based on accepting an assertion that the flightcrew will recognize and safely accommodate the loss of the normal means to control engine thrust, including shutting down the affected engine via an independent fuel shutoff, as required. However, recent engineering studies and service experience, including a 1997 Saudi Arabian Airlines Boeing 737-200 accident, indicate this traditionally accepted assertion is not always valid. For those airplanes re-evaluated to date, the available failure recognition and accommodation time under certain anticipated operating conditions is so short and the required corrective actions sufficiently unnatural that the flightcrew cannot be relied upon to reliably and completely perform those actions before the safe operation of the airplane is jeopardized.

While the focus of this petition was on the impacts of this determination on compliance with the general objective requirement of §25.901(c) relating to single failures, the FAA recognizes that this determination may have a similar impact on compliance with other more specific regulations, such as: §§21.21, 25.107, 25.109, 25.125, 25.143, 25.145, 25.147, 25.149, 25.161, 25.251, 25.571, 25.901, 25.903, and 25.1309. The FAA has concluded that, by addressing all the potential impacts of this determination on compliance with the general requirements of §25.901(c), we will inherently cover the scope of potential impacts on all other applicable regulations.

Further, the FAA recognizes that the bases of certification for some existing Gulfstream Model G-1159 and G-IV airplanes do not include the current §25.901(c). However, they do include predecessor regulations, such as §25.1309(b), CAR 4b.606(b), and

CAR 4b.400(b) with comparable intent. The justification for granting this exemption to §25.901(c) is equally applicable to these predecessor regulations. Consequently, while this documentation and the resultant granting specifically discuss only §25.901(c), they implicitly cover all applicable regulations impacted by this determination.

The FAA is responding to the full scope of this determination by developing a “Thrust Control Malfunction Airworthiness Program” to consistently and objectively assess and manage the existing and future transport airplane fleet risks associated with this endemic potential for non-compliance and unsafe conditions. The ultimate goal of this program will be to bring the transport airplane fleet back into compliance as quickly as practicable. The interim goal of this program will be to manage the risk associated with each instance of non-compliance so that it does not represent an unsafe condition.

For type certification, the FAA has begun requesting more effective validation of any assertion that the flightcrew will recognize and safely accommodate the loss of the normal means to control engine thrust. A series of such requests is what led Gulfstream to submit the subject petition. Until practicable design solutions can be identified, validated, and safely integrated into turbine engine control system type designs, it is clearly in the public interest to continue to certificate type design improvements, even if they do not strictly comply with the reference standard.

Gulfstream Models under Type Certificate A12EA

This partial exemption is applicable to all Gulfstream Model G-1159, G-1159A, G-1159B, G-IV, GV and GV-SP type design changes to be approved under Type Certificate Number A12EA after the date of this granting.

A related partial exemption (Exemption No. 8004) was previously granted specifically to allow the installation of BMW-Rolls Royce BR700-710C4-11 engines on GV-SP airplanes.

Exemption No. 8004 is not applicable to any other GV-SP type design changes. While the request for this more generally applicable exemption did not specifically call out the Model GV-SP, it is clear from the context of both the letter and the petition that Gulfstream intended “all Gulfstream Models under Type Certificate Number A12EA” to be covered by such an exemption. Consequently, the FAA has added the Model GV-SP to the applicability of this exemption.

For all such Gulfstream Aerospace type design changes, the petitioner intends to demonstrate that those combinations of failures that could jeopardize safe operation comply with § 25.901(c) in that they are not “probable combinations¹.” Conversely, the petitioner does not always intend to demonstrate that those single failures which could jeopardize safe operation comply with § 25.901(c).

¹ The term “probable,” as used in § 25.901(c) has a very different meaning from the same term as subsequently used in association with § 25.1309(b) compliance. As used in §25.901(c), “probable” means “foreseeable.” In §25.1309(b) terms, this means the subject failure conditions are “anticipated to occur” (i.e., are not “extremely improbable”).

Compliance with § 25.901(c) requires that each identified single failure be assumed to occur under all anticipated combinations of airplane operating and environmental conditions. While the single failures themselves must be assumed to occur regardless of their probability,² probability can be considered when determining what combinations of operating and environmental conditions are anticipated to occur in the fleet life of the airplane type. Single failures do not need to be assumed to occur under conditions that are in and of themselves not expected to occur.

All of the Gulfstream Aerospace models currently certificated under Type Certificate Number A12EA are known to have single failures that will cause uncontrollable high thrust. Consequently, it is expected that some, if not all, future derivatives of these designs may also have such non-compliant single failures. Uncontrollable high thrust under certain anticipated takeoff and landing conditions is expected to jeopardize the safe operation of these derivative Gulfstream Aerospace airplanes.

In order to certificate such derivative Gulfstream Aerospace airplanes, the petitioner must either obtain this partial exemption or substantially modify the type designs before any such derivative designs, including obvious product improvements, can be approved. As delineated in the petitioner's supporting information, the petitioner contends that having the partial exemption available as a certification option when design changes don't increase the risks associated with the subject non-compliance is in the best interest of the public.

As stated in the petition, "The engine control systems for the existing variants of the Gulfstream A12EA designs are all modern FADEC based systems, and, as such, future design changes to these control systems should provide opportunities to significantly reduce or even eliminate the subject non-compliance." The conditions established by the FAA for granting this partial exemption, when applied to each proposed design change, are intended to take full advantage of each practicable opportunity for improvement while affording the petitioner all warranted flexibility to certificate non-compliant derivative designs.

II. INTRODUCTION

To obtain this partial exemption, the petitioner must show, as required by § 11.81(d), that granting the request is in the public interest, and, as required by § 11.81(e), that the partial exemption will not adversely affect safety, or that a level of safety will be provided that is equal to that provided by the rules from which the partial exemption is sought.

III. PUBLIC INTEREST

If the FAA were to deny this petition, it would have the effect of preventing product improvements from being voluntarily proposed. The petitioner will be required by the conditions for granting this partial exemption to demonstrate that all practicable actions have

² While probability has been an acceptable means of supporting a finding that a particular "combination" of failures are not "probable," any single failure where the physics of the failure can be identified is typically "anticipated to occur," unless that occurrence within the relevant exposure can be clearly and acceptably ruled out, as is the case for those structural failures specifically excepted by the rule itself.

been taken to minimize the adverse effect on safety associated with granting this partial exemption from § 25.901(c) for each applicable design change. This condition assures that granting the partial exemption will be in the public interest. That is, any risks associated with a known non-compliance must be eliminated or further reduced wherever the FAA finds that to do so is technologically feasible and cost beneficial for the public. This has traditionally been accepted as the level of safety which is “in the public interest.” Furthermore, if bringing the airplane into compliance is found to be a “practicable action,” then this partial exemption would in effect be self eliminating.

In consideration of the above, the FAA concludes that granting this petition is inherently in the public interest.

IV. EFFECT ON SAFETY

The petitioner will be required by the conditions for granting this partial exemption to demonstrate that the risks due to uncontrollable high thrust failure conditions on any airplane certificated under this partial exemption will not exceed those currently known and accepted for comparable existing transport category airplanes. Making this a condition of this partial exemption, in combination with the condition to minimize that risk, means that granting this partial exemption should not adversely affect and, in fact, should improve the average per flight hour risk within the current transport airplane fleet.

For those existing transport airplanes re-evaluated to date, the conditions under which an uncontrollable high thrust failure may jeopardize the safe operation of the airplane are limited to specific aborted takeoff or approach and landing scenarios. Given that these scenarios occur, there is still a low probability that any serious injury will result. This limited exposure, in conjunction with the historically low occurrence rates, make this a relatively low per flight hour risk. This assessment is supported by the fact that the 1997 Saudi Arabian Airlines Boeing 737-200 accident is the only one attributed to these types of failures and that there were no serious injuries in that accident.

It is the spectre of this low per flight hour risk accumulating indefinitely on many, if not most, existing and future transport airplanes that is the primary concern driving development of the FAA “Thrust Control Malfunction Airworthiness Program.” To date, corrective actions under 14 CFR part 39 have been deemed warranted only when the uncorrected risks for a particular type design were considered significantly greater than the limited risks that result from the conditions and limitations of this partial exemption. Given that these conditions and limitations require that any airplane certificated under this partial exemption be expected to have an uncontrollable high thrust failure rate over three times better than the current fleet average, the impact of adding fleet hours of design changes to Gulfstream airplanes under Type Certificate Number A12EA to the overall transport fleet exposure should be insignificant. Furthermore, if as part of the “Thrust Control Malfunction Airworthiness Program,” the FAA determines that additional generally applicable precautions must be taken, including perhaps some future introduction of a compliant design, these will further minimize any cumulative risk impact of granting this partial exemption.

This partial exemption inherently implies a somewhat greater hazard than full compliance with § 25.901(c). This is why the FAA intends to bring the transport fleet back into full compliance as soon as practicable. Nevertheless, the fact that the per flight hour risks associated with this non-compliance are low allows us to develop a well considered recovery program to assure that we don't introduce a problem which is worse than the one we are trying to solve and that this recovery program is clearly in the public interest.

In consideration of the above, the FAA concludes that granting this petition will not adversely affect safety.

The Partial Grant of Exemption

In consideration of the foregoing, I find that a partial grant of exemption is in the public interest and will not adversely affect safety. Therefore, pursuant to the authority contained in 49 U.S.C. 40113 and 44701, delegated to me by the Administrator, Gulfstream Aerospace Corporation is granted a partial exemption from § 25.901(c) to the extent necessary to allow type certification of all Gulfstream Aerospace Model G-1159, G-1159A, G-1159B, G-IV, GV, and GV-SP type design changes to be approved under Type Certificate A12EA after the date of this granting without an exact showing of compliance with the requirements of § 25.901(c) or other applicable regulations as they relate to single failures resulting in uncontrollable high thrust conditions. This partial exemption is subject to the following conditions and limitations:

1. For any airplane certificated under this partial exemption, Gulfstream Aerospace Corporation must demonstrate, in accordance with an FAA-approved "Airworthiness Assessment and Risk Management Plan," that all practicable actions have been taken to minimize the adverse effects on safety associated with granting this petition. These must include, but are not limited to, practical actions to eliminate or further reduce the risks by improving designs, procedures, training, and instructions for continued airworthiness.
2. Gulfstream Aerospace Corporation must demonstrate, in accordance with an FAA-approved "Airworthiness Assessment and Risk Management Plan," that the risks associated with exempting the "uncontrollable high thrust failure condition" from the single failure provisions of § 25.901(c) are no greater for any airplane certificated under this partial exemption than those currently known and accepted for comparable existing transport category airplanes. Acceptable risk for this provision can be characterized as:
 - a. The airplane complies with § 25.901(c) for any foreseeable uncontrollable high thrust failure conditions in flight, except possibly during approach below 400 feet; and
 - b. The expected frequency of occurrence of the uncontrollable high thrust failure condition is less than one per ten million airplane operating hours.

3. The following “Note” will be added to the airplane Type Certification Data Sheet for any airplane certificated under this partial exemption:

“The FAA has concluded that the occurrence of any uncontrollable high thrust failure condition, or any of the associated causal failures listed within Gulfstream Aerospace Document (reference tbd), “may endanger the safe operation of an airplane” and hence are reportable under §§ 121.703 (c), 125.409 (c), and 135.415(c).”

In support of this “Note,” Gulfstream Aerospace must develop and obtain FAA approval of “Gulfstream Aerospace Document (reference tbd)” which lists those failures that can contribute to or cause an uncontrollable high thrust failure condition covered by this partial exemption. This document must then be made available as part of the instructions for continued airworthiness. Further, the failures listed within this document must be added to the list of reportables under § 21.3 for any airplane certificated under this partial exemption.

4. The granting of this partial exemption does not relieve any regulatory obligation to identify and correct unsafe conditions related to uncontrollable high thrust failure conditions.

Note: Additional background and guidance regarding these provisions are provided in FAA Letter 02-112-02, dated October 19, 2001.

Issued in Renton Washington on October 8, 2003.

/s/ Ali Bahrami
Acting Manager
Transport Airplane Directorate
Aircraft Certification Service